



Seal. Track. Trace



RadioSecure™ SLA 4

Creatively innovated by using active RFID technology to **report status** via RS-SLM or RS IVM to a hosted web-based supply chain visibility and security system. Equipped with **security-tampering sensor**, any unauthorized unsealing or violation of pre-set parameters will trigger an immediate Event Reporting. This level of insight facilitates immediate action to be taken to ensure **integrity of supply chain**.

Key Features

- ⌘ Hassle-free Installation
- ⌘ Flexible cable with break load of 1000kgf to secure any types of cargo
- ⌘ Key Lock or Motor version to cater for different applications
- ⌘ Remote monitoring of cargo
- ⌘ Rugged and Industry approved device
- ⌘ <10s Alert Delivery time
- ⌘ Screw-free design to enhance security
- ⌘ Tampering Alerts
- ⌘ Geofencing Alerts
- ⌘ User-configurable location update interval

Benefits



Protect the integrity of Cargo

- Real time alerts and status update of the cargo allows recovery actions and minimize losses.



Automate Processes

- Automated system provides data to eliminate human error and automate container inspection.



Monitor Anytime, Anywhere

- Web-based system accessible via special credentials. Available on mobile application too.



Reduce Claims and Risk

- Utilize system data analytic for preventive measures



Improve Customer Service

- Deliver perishable goods safely and on-time, reducing cost and increasing efficiency.



Reports and Data Analysis

- Automatic one page report generation of every trip.

Application

Container | Rail Cargo | Reefer Container | ECTS | Cross Country Tracking

ENVOTECH NETWORK SDN BHD (657306-W)

EMAIL: presales@envotech.com.my

VISIT: www.envotech.com

CALL: +605-5278287



Seal. Track. Trace

Specification (Key Lock version)



Key Lock version enables user to physically secure the sealing by using a built-in Lock. Unsealing can only be done by a Key. This provides additional security layer that does not depend on network.

Model Number	RS-SLA	RadioSecure™ Seal Lock Asset
Version	SLA-k	Key Lock
Physical	L x W x D Standard Cable Length x Dia Weight per set Color	120mm x 90mm x 60mm 40cm x 3.5mm (Customization available upon request) 400g Black
Environmental	Operating Temperature Storage Temperature Humidity Weatherproofing	-30°C to 70°C -40°C to 80°C 95% non-condensing IP67
Wireless	Frequency Active Transmission Power RF Range	ISM 2.4Hz QFSK modulation <18dBm (»100mW) 500m L.O.S.
Electrical	Battery Battery Capacity Battery Type Active Current Drain Inactive Current Drain	Rechargeable Built in 1,200mAH Lithium Ion Polymer <50mA <0.02mA
Mechanical	Break Load Key Lock	>1000kgf Built-in Push Key Lock <ul style="list-style-type: none"> To Lock, do not require a key To Unlock, require a key
Accessories (add on option)	K-Flex 1.5 Starseal 150	1.5mm Cable Seal, 300 pc per carton 150mm Plastic Seal, 1000 pc per carton
Certification	CE FCC	Yes Yes

ENVOTECH NETWORK SDN BHD (657306-W)

EMAIL: presales@envotech.com.my

VISIT: www.envotech.com

CALL: +605-5278287



Seal. Track. Trace

Specification (Motor version)



Motor version enables user to physically seal by a build-in Motor. Sealing and Unsealing can only be done by sending a command to the RS-SLA. This provides additional security layer that requires OTA communication.

Model Number	RS-SLA	RadioSecure™ Seal Lock Asset
Version	SLA-m	Motor
Physical	L x W x D Standard Cable Length x Dia Weight per set Color	120mm x 90mm x 60mm 40cm x 3.5mm (Customization available upon request) 400g Black
Environmental	Operating Temperature Storage Temperature Humidity Weatherproofing	-30°C to 70°C -40°C to 80°C 95% non-condensing IP67
Wireless	Frequency Active Transmission Power RF Range	ISM 2.4Hz QFSK modulation <18dBm (»100mW) 500m L.O.S.
Electrical	Battery Battery Capacity Battery Type Active Current Drain Inactive Current Drain	Rechargeable Built in 1,200mAH Lithium Ion Polymer <120mA <0.02mA
Mechanical	Break Load Motor	>1000kgf DC Motor
Accessories (add on option)	K-Flex 1.5 Starseal 150	1.5mm Cable Seal, 300 pc per carton 150mm Plastic Seal, 1000 pc per carton
Certification	CE FCC	Yes Yes

ENVOTECH NETWORK SDN BHD (657306-W)

EMAIL: presales@envotech.com.my

VISIT: www.envotech.com

CALL: +605-5278287