

RS-MIT and I hock - hoce SNOTECH

RadioSecure™ Mit

Equipped with active technology, it reports real time status to a hosted web-based supply chain visibility and security system. In-built with smart sensors and logic, any activation and removal of RS-Mit triggers an immediate Event Reporting. Coupled with backend Al logic, it facilitates immediate action to be taken to ensure strict monitoring is in placed.

Key Features

X Activation & Removal Alerts

X Light-Weight & Reusable

X Magnetic Charging

X LED indication for low battery

Specification

Model Number	RS-Mit	RadioSecure™ Mit
Version	Mit	Mit
Physical	Face L x W x D	40mm x 55mm x 20mm
	Strap L x W x D	200mm x 25mm x 2mm
	Weight per set	200g
	Color	Black
Environmental	Operating Temperature	-30°C to 70°C
	Storage Temperature	-40°C to 80°C
	Humidity	95% non-condensing
	Weatherproofing	IPx5, water-resistance
Electrical	Battery	Rechargeable Built in 3.7Vdc
	Battery Capacity	450mAH
	Battery Type	Lithium Ion Polymer
	Active Current Drain	<50mA
	Inactive Current Drain	<0.02mA
Add On	Temperature Sensor	Yes
	Oximeter Sensor	Yes

ENVOTECH MIT SDN BHD (1422164-P)

EMAIL: presales@envotech.com.my **VISIT**: www.envotech.com **CALL**: +605-5278287