




Seal. Track. Trace



## RadioSecure™ SLM4

Intelligent Standalone Seal Lock Master uses active RFID technology, GSM, GPRS and GPS to **report real time location and status** to a hosted web-based supply chain visibility and security system. Equipped with **security-tampering sensor**, any unauthorized unsealing or violation of pre-set parameters will trigger an immediate Event Reporting. This level of insight facilitates immediate action to be taken to ensure **integrity of supply chain**.

### Key Features

- ✎ Hassle-free Installation
- ✎ Flexible cable with break load of 1000kgf to secure any types of cargo
- ✎ Remote monitoring of cargo
- ✎ Rugged and Industry approved device
- ✎ <10s Alert Delivery time
- ✎ Tampering Alerts
- ✎ Geofencing Alerts
- ✎ User-configurable location update interval
- ✎ Long battery lifespan
- ✎ OTA Firmware Upgrade and Parameters Configuration

### Benefits



#### Protect the integrity of Cargo

- Real time alerts and status update of the cargo allows recovery actions and minimize losses.



#### Automate Processes

- Automated system provides data to eliminate human error and automate cargo inspections.



#### Monitor Anytime, Anywhere

- Web-based system accessible via special credentials. Available on mobile application too.



#### Reduce Claims and Risk

- Utilize system data analytic for preventive measures



#### Improve Customer Service

- Deliver perishable goods safely and on-time, reducing cost and increasing efficiency.



#### Reports and Data Analysis

- Automatic one page report generation of every trip.

### Application

Container | Rail Cargo | Reefer Container | Tarpaulin Truck | ECTS | Cross Country Tracking

**ENVOTECH NETWORK SDN BHD (657306-W)**

**EMAIL:** presales@envotech.com.my

**VISIT:** www.envotech.com

**CALL:** +605-5278287



Seal. Track. Trace

## Specification (EU 2G/LTE version)

Model Number	RS-SLM	RadioSecure™ Seal Lock Master
<b>Version</b>	RS-SLM4	RadioSecure™ Seal Lock Master4
<b>Physical</b>	L x W x D Standard Cable Length Weight per set Color	164mm x 104mm x 46.5mm 16'' 600g Black
<b>Environmental</b>	Operating Temperature Storage Temperature Humidity Weatherproofing	-30°C to 70°C -40°C to 80°C 95% non-condensing IP67
<b>Wireless</b>	Frequency Active Transmission Power RF Range BLE	ISM 2.4Hz QFSK modulation <18dBm (»100mW) 500m L.O.S. Yes
<b>GPRS</b>	GSM Bands LTE-FDD LTE-TDD SIM Failover	B2/B3/B5/B8 B1/B3/B5/B7/B8/B20/B28 B38/B40/B41 Dual Nano SIM slots (Primary & Secondary) 4G failover to 2G/SMS
<b>Satellite Constellation System</b>	GPS Sensitivity Position Accuracy Acquisition Time (Hot Start) Maximum Velocity Speed accuracy GPS Beidou Antenna	-162dBm to -165dBm Autonomous 5m 1s <515m/s 0.1 m/s Yes Yes Built-In active Antenna
<b>Memory Capacity</b>	Internal Flash Memory External Flash Memory	512KB 16MB
<b>Electrical</b>	Battery Battery Capacity Battery Type Active Current Drain Inactive Current Drain	Rechargeable Built in 10,500mAH Lithium Ion <300mA <3mA

**ENVOTECH NETWORK SDN BHD (657306-W)**

**EMAIL:** presales@envotech.com.my

**VISIT:** www.envotech.com

**CALL:** +605-5278287



Seal. Track. Trace

## Specification (Asia 2G/LTE version)

Model Number	RS-SLM	RadioSecure™ Seal Lock Master
<b>Version</b>	RS-SLM4	RadioSecure™ Seal Lock Master4
<b>Physical</b>	L x W x D Standard Cable Length Weight per set Color	164mm x 104mm x 46.5mm 16'' 1000g Black
<b>Environmental</b>	Operating Temperature Storage Temperature Humidity Weatherproofing	-30°C to 70°C -40°C to 80°C 95% non-condensing IP67
<b>Wireless</b>	Frequency Active Transmission Power RF Range BLE	ISM 2.4GHz QFSK modulation <18dBm (»100mW) 500m L.O.S. Yes
<b>GPRS</b>	LTE-FDD LTE-TDD GSM SIM Failover	B1/B3/B8 B34/B38/B39/B40/B41 B3/B8 Dual Sim Slot 4G Failover to 2G/SMS
<b>Satellite Constellation System</b>	GPS Sensitivity Position Accuracy Acquisition Time (Hot Start) Maximum Velocity Speed accuracy GPS Beidou Antenna	-162dBm to -165dBm Autonomous 5m 1s <515m/s 0.1 m/s Yes Yes Built-In active Antenna
<b>Memory Capacity</b>	Internal Flash Memory External Flash Memory	512KB 16MB
<b>Electrical</b>	Battery Battery Capacity Battery Type Active Current Drain Inactive Current Drain	Rechargeable Built in 10,500mAH Lithium Ion <300mA <3mA

**ENVOTECH NETWORK SDN BHD (657306-W)**

**EMAIL:** [presales@envotech.com.my](mailto:presales@envotech.com.my)

**VISIT:** [www.envotech.com](http://www.envotech.com)

**CALL:** +605-5278287